

HORIBA

Explore the future

COMPACT NITRATE
ION METER**twinNO₃⁻**
B-340 Series

HORIBA's flat sensor enables easy measurement with only a few drops of sample

Simple, Accurate, Rapid Measurement!

Waterproof body

Just drop the sample directly on the sensor

Easy to read LCD display

Actual size

Measurement button

ON/OFF button

Calibration button

The B-340 series is a compact and robust nitrate ion meter using HORIBA's revolutionary flat sensor technology. This technology allows very small sample sizes to be measured (minimum sample size 0.3mL). The instrument is simple to calibrate and easy to use. Combine this with its compact pocket size and you have an instrument that can be used for various applications in the lab or out in the field.

- Waterproof*
- Automatic calibration function (selection of 1-point, 2-point calibration)
- Wide measuring range
- Flat sensor enables measurements of small sample volumes (0.3mL)
- Special setting modes (temperature measurement, voltage measurement, compensation function etc)
- Selectable analysis of NO₃⁻ or NO₂⁻-N
- Selectable units (ppm, mg/L, kg/10a)

* The instrument may not be used when totally submerged underwater



Specifications

Model	B-341 (for crops)	B-342 (for soil)	B-343 (for general use)	
Measurement principle	Ion electrode method			
Sample volume required for measurement	0.3 mL to 2.0 mL			
Measurement range	NO ₃ ⁻	100 to 9900 (ppm or mg/L)	30 to 600 (ppm or mg/L)	62 to 6200 (ppm or mg/L)
	NO ₃ ⁻ -N	23 to 2200 (ppm or mg/L-N)	6.8 to 140 (ppm or mg/L-N)	14 to 1400 (ppm or mg/L-N)
	NO ₃ ⁻ -N *1	-	3.4 to 68 (kg/10a)	-
Calibration method	One calibration to 5000 ppm (two calibrations to 300 ppm and 5000 ppm)	One calibration to 300 ppm (two calibrations to 30 ppm and 300 ppm)	One calibration to 2000 ppm (two calibrations to 150 ppm and 2000 ppm)	
Reproducibility	± 10% *2			
Display	4-digit digital LCD display			
Power	CR2032 batteries (x2)			
Waterproof standard	IP67 *3			
Auto power OFF	30 minutes			
Outer dimensions	165 mm x 29 mm x 19 mm (excluding projections)			
Mass	Approx. 52 g (meter only)			
Operating temperature/humidity	5°C to 40°C, 85% relative humidity max. (no condensation)			
Operation switches	3 switches (power, calibration, measurement)			

*1 With soil/water sampling ratio of 1:5.

*2 Using HORIBA's prescribed method.

*3 No failure when submerged in water at a depth of 1 meter for 30 minutes. The meter cannot be used underwater.



B-341 and B-342 are kit products. For individual purchase of meters, please contact our sales representatives.

HORIBA continues contributing to the preservation of the global environment through analysis and measuring technology.



Please read the operation manual before using this product to assure safe and proper handling of the product.

- The contents of this catalog are subject to change without prior notice, and without any subsequent liability to this company.
- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.
- All brand names, product names and service names in this catalog are trademarks or registered trademarks of their respective companies.

<http://www.horiba.com> e-mail: info@horiba.co.jp

● HORIBA, Ltd.

Head Office
Miyano Higashi, Kisshoin
Minami-ku, Kyoto, Japan
Phone: 81 (75) 313-8123
Fax: 81 (75) 321-5725

Tokyo Sales Office
1-7-8 Higashi-Kanda
Chiyoda-ku, Tokyo, Japan
Phone: 81 (3) 3861-8231
Fax: 81 (3) 3861-8259

TAIWAN Representative Office
3F, NO.18 Lane 676, Chung
Hua Rd, Chupei City,
Hsinchu Hsien, 302, Taiwan
Phone: 886 (3) 656-1012
Fax: 886 (3) 656-8231

● HORIBA TRADING (SHANGHAI) CO., Ltd.

Shanghai Office
Room 1701, United Plaza,
1468 Nanjing Rd. West,
Shanghai, 200040, China
Phone: 21-6289-6060
Fax: 21-6289-5553

Beijing Office
Room 1801, Capital Tower,
Beijing, Tower 1 No.6Jia,
Jianguomenwai Ave.,
Chaoyang District, Beijing,
100022 China
Phone: 10-8567-9966
Fax: 10-8567-9066

● HORIBA KOREA Ltd.

112-6 Sogong-Dong
Choong-ku, Seoul, Korea
Phone: 82 (2) 753-7911
Fax: 82 (2) 756-4972

● HORIBA INSTRUMENTS Pte. LTD.

10 Ubi Crescent
#05-11/12, Ubi Techpark
Singapore 408564
Phone: 65 6745-8300
Fax: 65 6745-8155

● HORIBA INSTRUMENTS INCORPORATED

Irvine Facility
17671 Armstrong Avenue
Irvine, CA 92614, U.S.A.
Phone: 1 (949) 250-4811
Fax: 1 (949) 250-0924

Ann Arbor Facility
5900 Hines Drive
Ann Arbor, MI 48108
U.S.A.
Phone: 1 (734) 213-6555
Fax: 1 (734) 213-6525

● HORIBA / STEC INCORPORATED

HORIBA Technology Center
3265 Scott Boulevard
Santa Clara, CA 95054
U.S.A.
Phone: 1 (408) 730-4772
Fax: 1 (408) 730-8975

● HORIBA GmbH

Kaplanstrasse 5
A-3430 Tulln,
Austria
Phone: 43 (2272) 65225
Fax: 43 (2272) 65230

HORIBA CZECHIA

Organizace slozka Praha
Petrohradská 13
CZ-101 00 Praha 10, Czech Republic
Phone: 420 (2) 717-464-80
Fax: 420 (2) 717-470-64

● HORIBA INSTRUMENTS LIMITED

Kyoto Close
Summerhouse Road
Moulton Park, Northampton
NN3 6FL, U.K.
Phone: 44 (1604) 542500
Fax: 44 (1604) 542699

● HORIBA EUROPE GmbH

Head Office
Hans-Mess-Str.6
D-61440 Oberursel/Ts.
Germany
Phone: 49 (6172) 1396-0
Fax: 49 (6172) 137385

Leichlingen Facility
Julius-kronenberg Strasse
D-42799 Leichlingen
Germany
Phone: 49 (2175) 8978-0
Fax: 49 (2175) 8978-50

HORIBA SWEDEN
Sydhavnsvägen 55-57,
SE-151 38 Södertälje,
Sweden
Phone: 46 (8) 550-80701
Fax: 46 (8) 550-80567

● HORIBA FRANCE

12, Avenue des Tropiques
91955 LES ULIS
France
Phone: 33 (1) 69-29-96-23
Fax: 33 (1) 69-29-95-77

● HORIBA Jobin Yvon

SRL Torino Office
Europalace
Corso Torino 43/45
10043 Orbassano, Torino
Italy
Phone: 39 (011) 9040601
Fax: 39 (011) 9000448

Bulletin:HRE-1164B

Printed in Japan ZY-TH(SK)53